

MATERIAL SAFETY DATA SHEET

Manufactured for:

Edelman – Powered by Crypton

6745 Daly Road
West Bloomfield, MI 48322
Telephone: 1 (800) CRYPTON
Emergency Telephone: (800) 279-7866

N.P.C.A. Rating Scale	
4	= Extreme
3	= High
2	= Moderate
1	= Slight
0	= Insignificant

Health: 0
Fire: 0
Reactivity: 0

Section 1 - IDENTIFICATION

Product Name: Edelman Leather Cleaner CC# 0249

Date Prepared: 8-19-06

Chemical Family: Water Based Cleaner
Proper D.O.T. Shipping Name: Liquid Cleaning Compound

Section 2 – INGREDIENTS/IDENTITY INFORMATION
(Hazardous Ingredients as Defined by OSHA, 29 CFR 1910.1200)

% By Wgt.	Material	P.E.L. Skin	T.L.V. Skin	CAS No.
<10%	Sodium Metasilicate Penta Hydrate	N/E	N/E	6834-92-0
5%	Sodium Xylene Sulfonate	N/E	N/E	1300-72-7

The specific formula of this product is not regulated under CERCLA or RCRA. This product is not reportable under SARA Title III Section 311/312. The balance of ingredients are not considered to be hazardous within the meaning of the OSHA Hazardous Communication Standard, and are held as proprietary trade secrets. ITEMS MARKED * ARE SARA TITLE III SEC 313 REPORTABLES. ALL INGREDIENTS ARE ON TSCA INVENTORY.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	>212° F
SPECIFIC GRAVITY	1.05
EVAPORATION RATE (Butyl Acetate =1)	1
SOLUBILITY IN WATER	Complete
APPEARANCE AND ODOR	Clear Liquid, No Fragrance
pH	7.0 – 8.0

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (TCC): >200° F
FLAMMABLE LIMITS – N/A
EXTINGUISHING MEDIA – Water or suitable material for primary source of fire
SPECIAL FIRE FIGHTING PROCEDURES – None
UNUSUAL FIRE AND EXPLOSION HAZARD – None

SECTION 5 - REACTIVITY DATA

STABILITY – Stable CONDITIONS TO AVOID – Excessive heat
INCOMPATIBILITY (MATERIALS TO AVOID) – Strong oxidizing agents and acidic agents
HAZARDOUS DECOMPOSITION OR BYPRODUCTS – Smoke may be acrid and fume irritating. Burning may produce carbon dioxide and/or carbon monoxide
HAZARDOUS POLYMERIZATION – None described
CONDITIONS TO AVOID FOR POLYMERIZATION – Polymerization catalysts such as aluminum chloride and acidic clays

SECTION 6 - HEALTH HAZARD DATA

ROUTES OF ENTRY: EYES (X) SKIN (X) INGESTION (X) INHALATION (X)
HEALTH HAZARDS (ACUTE AND CHRONIC):
ACUTE: May be irritating to eyes and skin. Inhalation can cause irritation.
CHRONIC: None known.
CARCINOGENICITY: NTP, IARC MONOGRAPHS, OSHA REGULATED? No
SIGNS AND SYMPTOMS OF EXPOSURE – Eyes: Direct contact will cause irritation. Skin: Prolonged skin contact may cause irritation.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE- None known.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician.
SKIN: Flush skin with water. Contact a physician if irritation occurs.
SWALLOWING: Drink water or milk. Do not induce vomiting. Contact a physician.
INHALATION: If symptoms occur, evacuate to fresh air. If symptoms persist, contact a physician.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED – Absorb spilled material with dirt, sand or other suitable absorbent and sweep up.
WASTE DISPOSAL METHOD – Dispose in accordance with all regulations.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING – None

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION – Not required with normal usage. VENTILATION – Normal room ventilation.
PROTECTIVE GLOVES – Rubber Gloves EYE PROTECTION – Chemical splash goggles recommended.